


PRODUCT NO.: 050987

PRODUCT: UNIAXIAL GRID




PHYSICAL CHARACTERISTICS:	
STRUCTURE	Monororiented geogrids
POLYMER	HDPE
COLOUR	Black
UV STABILISED	Yes

DIMENSIONAL CHARACTERISTICS:	
WIDTH	1 m
LENGTH	100m
WEIGHT PER M ²	350g (+/- 5%)
MESH SIZE (MD x TD)	Egg-shaped holes 120 x 10/20 mm

TECHNICAL CHARACTERISTICS:	
Measurement	Results
TENSILE STRENGTH AT MAXIMUM LOAD (MD)	45.0 kN/m
STRENGTH AT 2% ELONGATION (MD)	14.8 kN/m
STRENGTH AT 5% ELONGATION (MD)	27.7 kN/m
YIELD POINT ELONGATION (MD)	11.0%

For and on behalf of Boddingtons Limited



Quality Manager

All the above information is given in good faith, but the figures are typical values only and should not be taken as a guarantee of performance. Manufacturing tolerances for dimensional and technical characteristics apply and are available on request. The company reserves the right to improve the product and adjust the specification without notice.

SPEC 050987
Issue: 1
Page 1 of 1
Date: 22.05.07



Certificate No. FM 33039

BODDINGTONS LIMITED

Blackwater Trading Estate • The Causeway • Maldon • Essex CM9 4GG • England
Tel: +44 (0) 1621 874200 Fax: +44 (0) 1621 874299
e.mail: sales@boddingtons-ltd.com • www.boddingtons-ltd.com